

CHAIN BLOCK

- ※ Japan technology
- ※ Load limiter is available at extra cost
- ※ Low effort to lift maximum load
- ※ Automatic double pawl braking system
- ※ Premium grade alloy load chain and zinc plated hand chain as standard
- ※ Drop forged and expertly heat treated hooks for great strength and long wearing
- ※ Capacity ranges from 0.5t to 20t, heavy duty 30t, 50t is available



Model	HSZ-A _{1/2}	HSZ-A1	HSZ-A1 _{1/2}	HSZ-A2	HSZ-A3	HSZ-A5	HSZ-A10
Capacity(t)	0.5	1	1.5	2	3	5	10
Standard lift(m)	2.5	2.5	2.5	3	3	3	3.5
Test load(t)	0.75	1.5	2.25	3	4.5	7.5	15
Min.distance between hooks(mm)	285	315	340	380	475	600	700
Chainpull to lift full load(n)	25	33	34	34	35	39	41
No.of load chain fall lines	1	1	1	1	2	2	4
Diameter of load chain(mm)	6.3	6.3	7.1	8	7.1	9	9
Net weight(kg)	8.4	11	13.5	21	22	40	77
Gross Weight(kg)	9.4	12	14.5	22	23	41.5	85
Packing measurement LxWxH(cm)	30x17x32	30x17x32	30x17x32	28x19x23	30x17x32	40x20x34	62x50x26